

TERMINAL BOX MODEL 12STB



Dimensions (mm)	225*302*71	
Material	ABS/PC UV Resistant	
Fiber capacity	24 SC SIMPLEX	
IP Rating	65	
Operating Temperature (°C)	-40°C ~ +85°C	
Cable input port	Max. 2 ports (Max. diameter: 12mm)	
Cable output capacity	Max. 24 ports (Max. diameter: 3mm)	
OTB Resin	Tensile Strength	≥ 450kg/n2, @10mm/min
	Impact Strength	35 kgcm/n2 (normal temp.)
	Flexural Strength	≥ 450kg/n2, @10mm/min
Standards	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754	

Part Number	Nr. of ports
12STB12	12 SC Simplex
12STB24	24 SC Simplex

HONG KONG

Romatecsans International Limited
7/F., Catic Building, No. 44 Tsun Yip
Street, Kowloon, Hong Kong
Tel. +852 8199 9706
asia@romatecsans.com

CHILE

Importadora y Exportadora Romatecsans Ltda.
Carmen Farina 6758, Vitacura,
Santiago, Chile
Tel.: +56 22 9797 922
ventas@romatecsans.com

sales@romatecsans.com
www.romatecsans.com

