

TERMINAL BOX MODEL 27STB

Description

27STB fiber access termination box is able to hold up to 16 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Features

- Water-proof design with IP-66 Protection level.
- Integrated with flap-up splice cassettes with splitter tube holder Maximum 96F splice capacity
- Plug-and-play installation, easy for maintenance and expansion.
- Fiber bend radius control more than 40mm.
- 180 degree access with buckled lock structure.
- 2 pcs 1*8 or 1*16 PLC splitter can be installed in splice tray as option.
- 16 pcs of pre-installed Huawei compatible reinforced water-proof SC adapter.
- 1 mid- span cable entrance (10-16.5mm) for uncut cable and 2 reserved cable entrance for distribution cable (8-16.5mm).



Dimensions (mm)	345*220*95
Material	ABS/PC UV Resistant
Fiber capacity	96 Fibers (4 trays * 24F)
IP Rating	66
Operating Temperature (°C)	-40°C ~ +85°C
Cable input port	Mid Span of 10 ~ 16.5mm
Aplication	Wall mounted Pole mounted Aerial hanging
Standard accessories	Splice cassette and cable management tool, installation nuts and bolts, protection sleeves, hose clamp, cable tube, key, wrench, rubber seal for cable entrance.
Optional accesories	Pole mounted kit + aerial hanging kit
Compatibility	IPRS (Huawei)

Pictures

