

FIBER OPTIC TERMINAL BOX MODEL 2EUTB

Our Terminal Boxes are applicable in the straight through or branch connection of indoor cable.
Indoor wiring terminal box Inner clip design is used for easy operation.
Max capacity cores of 4 SC Simplex.



Dimensions (mm)	150*110*35
Material	ABS
Weight (kg)	0.2
Operating Temperature (°C)	-25°C ~ +45°C
Packing	1 box of 48*25*39cm : 60 units

ORDERING INFORMATION											
Type	Adapter	Polishing		Type	Colors		Ports	Fiber		Length (m)	
2EUTB	FC	A	<i>APC</i>	D	<i>Duplex</i>	1	<i>Aqua</i>	1	OS1	<i>G.652B</i>	1
	E2000	U	<i>UPC</i>	Q	<i>Quad</i>	2	<i>Blue</i>	2	OS2	<i>G.652D</i>	2
	LC			S	<i>Simplex</i>	3	<i>Beige</i>	3	655	<i>G.655</i>	3
	MU					4	<i>Green</i>	4	657	<i>G.657</i>	
	SC					5	<i>12 colors</i>		OM1	<i>62.5/125</i>	
	ST					6	<i>Yellow</i>		OM2	<i>50/125</i>	
								OM3	<i>50/125</i>		
								OM4	<i>50/125</i>		

ORDERING INFORMATION EXAMPLE

2EUTB	SC	U	S	6	1	OS2	1
--------------	-----------	----------	----------	----------	----------	------------	----------

Configuration: Indoor terminal box Model 2EUTB SC UPC SX 1 Yellow OS2 1mt pigtail