

TECHNICAL SPECIFICATION

FIBER OPTIC TERMINAL BOX MODEL 4EUTB

Terminal Box Applicable in the straight through or branch connection of indoor cable.
Available for the distribution and terminal connection of various kinds of optical fiber system.
Max capacity cores of 16 with LC DX (8* FC/SC/ST SX).



Dimensions (mm)	265*155*45
Material	Cold rolled steel
Cable entries	2 entries PG13.5 - 6-12mm
Weight (kg)	1.05
Pressure Resistance	500N
Shock Resistance	750N
Operating Temperature(°C)	-40°C~+75°C

ORDERING INFORMATION

Type	Adapter	Polishing	Type	Colors	Ports	Fiber	Length (m)
4EUTB	FC	A APC	D Duplex	1 Aqua	1	OS1 G.652B	1
	E2000	U UPC	Q Quad	2 Blue	2	OS2 G.652D	2
	LC		S Simplex	3 Beige	3	655 G.655	3
	MU			4 Green	657 G.657	
	SC			5 12 colors	7	OM1 62.5/125	
	ST				8	OM2 50/125	
						OM3 50/125	
						OM4 50/125	

ORDERING INFORMATION EXAMPLE

4EUTB	LC	U	D	5	6	OS2	1
-------	----	---	---	---	---	-----	---

Configuration: Indoor terminal box Model 4EUTB LC UPC DX 6 12 Colors OS2 1mts pigtails (4EUTBLCUD56OS21)

HONG KONG

Tel. +852 3678 6747
sales@romatecsans.com

CHILE

Tel.: +56 22 2187258
ventas@romatecsans.com

SPAIN

Tel.: +34 61222 4997
eu@romatecsans.com