

FIBER OPTIC SLIDING PATCH PANEL RS1

The RS1 fiber optic patch panel is designed in accordance with TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, RoHS, Reach and SvHC.




| | | | |
|-------------------------|-----------------------------------|------------------------|---------------------------------------|
| Material | Cold rolled steel 1.2mm thickness | Number of ports | 12 ~ 24 |
| Material Coating | Electrostatic painting | Capacity | Up to 72 fibers with LC Quad adapters |
| Height (mm) | 44.4 (1U) | Cable entries | 2*20mm & 2*25mm |
| Width (mm) | 483 | Weight (kg) | 2.5 |
| Depth (mm) | 205 | Operating Angle | 45° (picture) |
| IP Rating | IP20 | Operating T. | -40°C ~ +55°C |

Front Options


24 FC/ST Simplex Adapters



24 SC Simplex / LC Duplex Adapters



24 FC/ST Duplex Adapters



24 SC Duplex / LC Quad Adapters



ORDERING INFORMATION

| Model | Adapter | Polishing | Type | Colors | Ports | Fiber | Length (m) | |
|-------|---------|-----------|------|--------|-------|-------|------------|---|
| RS1 | FC | A | D | 1 | 1 | OS1 | 1 | |
| | | U | Q | 2 | 2 | OS2 | 2 | |
| | E2000 | | | S | 3 | 3 | 655 | 3 |
| | | | | | 4 | | 657 | |
| | LC | | | | 5 | 7 | OM1 | |
| | MU | | | | | 8 | OM2 | |
| | SC | | | | | | OM3 | |
| | ST | | | | | | OM4 | |

ORDERING INFORMATION EXAMPLE

| | | | | | | | |
|-----|----|---|---|---|---|-----|---|
| RS1 | LC | U | D | 5 | 6 | OS2 | 1 |
|-----|----|---|---|---|---|-----|---|

Configuration: Fiber Optic Sliding Patch Panel LC UPC 24 DX 48 Colors OS2 1mts pigtails

HONG KONG

Tel. +852 3678 6747

sales@romatecsans.com

CHILE

Tel.: +56 22 2187258

ventas@romatecsans.com

SPAIN

Tel.: +34 61222 4997

eu@romatecsans.com