

### PORTABLE OTDR M3

#### Features

- Touch screen + keypad, easy to operate
- Lithium battery support more than 10 hours continuous working
- Supporting data exchange between the SD card and USB flash drive
- One-click red-light switch-on function
- Solid shell design, dust proof and shock proof
- Small, light, and portable



Dynamic range (dB)	32/30
Wavelength (±20 nm)	1310/1550
Display	3.5" TFT LCD touch screen
Light source type	LD
Optical interface	FC/UPC
Distance range (km)	0.3, 1, 3, 5, 10, 30, 60, 120
Pulse width (ns)	5, 10, 20, 40, 80, 160, 320, 640, 1280, 2560, 5120, 10240, 20480, Auto
Measurement duration	15s, 30s, 1min, 2min, 3min
Attenuation dead zone	10m
Event dead zone	1.8m
Data storage	>60000 test traces
Communication interface	USB
VFL	650nm (Wavelength) / ≥-3 (Output power (dBm)) / 3km (Test distance)
Optical communications test	Yes
Size	220*106*60mm
Weight	0.88kg
Operating temperature	-10°C ~ +50°C
Relative humidity	0% ~ 95%

#### ORDERING INFORMATION

**RS-OTDRM3**

#### HONG KONG

Tel. +852 3678 6747

sales@romatecsans.com

#### CHILE

Tel.: +56 22 2187258

ventas@romatecsans.com

#### SPAIN

Tel.: +34 61222 4997

eu@romatecsans.com